

Available serv-Clip® measuring connectors											
For mounting on steel and <sup>(3)</sup> stainless steel pipelines –no cutting pipelines											
Type		SC-1-A-..		SC-1-P-..			SC-1-T-..		SC-1-P-..		
		SC-2-A-..		SC-2-P-..			SC-2-T-..		SC-2-P-..		
Housing size	for pipes with OD (mm)	Hydr. pipe DIN 2391		threaded pipe DIN			Tube-OD US Standard SAE cold-drawn		Pipe-ID US standard SAE warm rolled		
		ND mm	Pipe wall up to 5mm	ID R-Inches (approx.)	tube wall DIN 2440 medium heavy	DIN 2441 heavy	OD Inches	Pipe wall mm	ID Inches	Pipe wall Schedule 80	Schedule 160
I	9.52						3/8	1.2			
	10	10	L / S								
	(2) 12	12	L / S								
	12.7						1/2	2.1			
	13.5			R1/4	2.4	2.9			1/4	3.0	-
	14	14	S								
	15	15	L								
	15.9						5/8	2.5			
	16	16	S								
II	17.2			R3/8	2.4	2.9			3/8	3.2	-
	18	18	L								
	19.05						3/4	2.9			
	20	20	S								
	21.4			R1/2	2.65	3.25			1/2	3.7	4.7
	22	22	L								
	25	25	S								
III	25.4						1	3			
	26.9			R3/4	2.65	3.25			3/4	3.9	5.5
	28	28	L								
	30	30	S								
	31.75						1 1/4	3			
	33.7			R1	3.25	4.05			1	4.5	(1)6.4
	35	35	L								
IV	38	38	S								
	38.1						1 1/2	4			
	42	42	L								
	42.4			R1 1/4	3.25	4.05			1 1/4	4.85	(1)6.4
	48.3			R1 1/2	3.25	4.05			1 1/2	5.08	(1)7.14
	50	50	6								
	50.8						2	5			
V	60.3			R2	3.65	4.5			2	5.02	(1)7.46
	65	65	8								
	76.1			R2 1/2	3.65	4.5			2 1/2	7.01	
	88.9			R3	4.05	4.85			3	7.62	

(1)For ordering the PIPE (P) model between 1" to 2" please reconfirm us the schedule 80 or 160.  
 We deliver special mounting instructions / needle for schedule 160 upon request (no additional charge).  
 (2)The flow rate and leakage sensor can be used from pipe 12 x 1,5 mm to 5,5 mm wall thickness with the Pipe measuring point serv-Clip®. For pipes over 3" (88,9 mm) and wall thickness from 6 mm ask about our adapter SC-XE-607.  
 (3)We deliver a special needle for stainless steel pipelines only upon request (up to 5 mm wall thickness) with SC-1 and SC-2 possible.

Available in stock

Only in SC-2-.. available